

Generator Set Range

30 > 600 kVA



Model	50Hz-1500RPM -400V/230V						Dimensions		Fuel Tank	Weight (kg)
	PRP		LTP		Engine Model	Consumption Fuel 75% @ (l/h)	Open & Canopy			
	kVA	kW	kVA	kW						
IV.33	30	24	33	26,4	80313AM1P	5,6	2000x860x1500	60	800	
							2375x1125x1540	130/500	1050	
IV.44	40	32	44	35,2	R24MSNS01.40A01	N/A	2000x860x1500	60	850	
							2375x1125x1540	130	1000	
IV.50	45	36	50	40	NEF45AM2	9.8	2000x860x1500	60	850	
							2375x1125x1540	130/500	1100	
IV.66	60	48	66	52.8	NEF45SM1A	10.2	2000x860x1500	60	900	
							2375x1125x1540	130/500	1200	
IV.88	80	64	88	70.4	NEF45SM3	15.4	2000x1100x1530	60	1400	
							2675x1125x1645	190/1000	1600	
IV.110	100	80	110	88	NEF45TM2A	16.2	2000x1100x1530	80	1450	
							2675x1125x1645	190/1000	1800	
IV.132	120	96	132	105.6	NEF45TM3	21.6	2000x1100x1530	80	1500	
							2675x1125x1645	190/1000	1950	
IV.138	125	100	138	110.4	NEF67SM1	23.2	2900x1100x1650	350	1500	
							3500x1250x1900	350/500	2300	
IV.165	150	120	165	132	NEF67TE1PV	28.2	2900x1100x1650	350	1520	
							3500x1250x1900	350	2400	
IV.176	160	128	176	140.8	NEF67TM3A	29	2900x1100x1650	350	1520	
							3500x1250x1900	350/500	2400	
IV.187	170	136	187	149.6	NEF67TM4	29.4	2900x1100x1650	350	1520	
							3500x1250x1900	350/500	2400	
IV.220	200	160	220	176	NEF67TM7	37.3	2900x1100x1650	350	1900	
							3500x1250x1900	350/500	2500	
IV.275	250	200	275	220	NEF67TE8P	41.2	2900x1100x1650	350	2000	
							3900x1250x1900	350/500	2750	
IV.330	300	240	330	264	C87TE4	52.6	2900x1100x1650	350	2500	
							3900x1250x1900	350/500	3050	
IV.385	350	280	385	308	CURSOR13TE2A	57.3	3500x1250x2300	500	3000	
							4400x1650x2370	600/800/1000	3850	
IV.440	400	320	440	352	CURSOR13TE3A	70.4	3500x1250x2300	500	3050	
							4400x1650x2370	600/800/1000	3950	
IV.500	450	360	500	400	CR13TE6W	72.5	3500x1250x2300	500	3000	
							4400x1650x2370	600/800/1000	4150	
IV.550	500	400	550	440	CR13TE7W	80.2	3500x1250x2300	500	3000	
							4400x1650x2370	600/800/1000	4000	
IV.600	550	440	600	480	CR16TE1W	84.5	3500x1250x2300	500	3300	
							5000x1650x2370	800/1000/1250	4250	
IV.660	600	480	660	528	CR16TE1W	84.5	3500x1250x2300	500	3900	
							5000x1650x2371	800/1000/1250	4900	